

Powered by Relationships



Water Source Heat Pump

NOW IN STOCK!

SAME DAY PICK-UP OR DELIVERED IN 1-2 BUSINESS DAYS

CALL TODAY 978-225-2045

MARCH 2018

Aaon Unit Size (tons)	Unit Hand	Electrical			Efficiency		Dimensions	Rigging Weight	Aaon
		V-Ph-Hz	MCA	Max Fuse	EER	COP	L x W x H (In.)	(lbs)	Model Number
2	Right	208-230 / 1 / 60	19	30	15.1	3.75	43 x 22 x 17	158	WHA-024
2	Left	208-230 / 1 / 60	19	30	15.1	3.75	43 x 22 x 17	158	WHA-024
3	Right	208-230 / 1 / 60	25	40	15.2	3.71	48 x 22 x 21	179	WHA-036
3	Left	208-230 / 1 / 60	25	40	15.2	3.71	48 x 22 x 21	179	WHA-036
4	Left	208-230 / 1 / 60	34	50	16.8	3.97	54 x 24 x 21	239	WHA-048
5	Left	208-230 / 1 / 60	39	60	15.1	4.05	54 x 24 x 21	247	WHA-060
						Hose Kits (Aaon Match)	Pipe Size / GPM	Hose Length	TCA Part #
						WHA-024	3/4" / 0.5-9.0	36"	H63106
						WHA-036	1" / 10-25	36"	H83209
						WHA-048	1-1/4" / 10-25	36"	H932012
						WHA-060	1-1/4" / 10-25	36"	H932015



FEATURES

- All Aluminum Construction with Closed Cell Neoprene Insulation
- Aluminum Microchannel DX Air Coil
- Stainless Steel Drain Pan
- Induction Brazed Copper Piping Connections
- Left or Right Hand Return
- Left, Right or End Discharge
- Tool-less Service Access Panels
- Bottom Service Access
- Sellable or Recyclable Sheet Metal Pallet
- ECM Fan, Standard 2" MERV 8 Filter Rack
- 5 Year Parts Warranty - Standard!
- Optional Accessories Available including Hose Kits, Thermostats, Disconnect Switches